



DOMESTIC WATER KEY NOTES

EXTEND $2\frac{1}{2}''$ CW/ SOFT COPPER SUPPLY TO NEW MISTING SYSTEM. PROVIDE $3\frac{1}{2}''$ FTT BAL VALVE AND DOUBLE CHECK VALVE AT CONNECTION OF EXISTING CW SUPPLY. MOUNT $2\frac{1}{2}''$ CW COORDINATE EXACT LOCATION WITH CONSTRUCTION SUPERVISOR. DOUBLE CHECK VALVE ASSEMBLY SHALL BE EQUAL TO A WATTS SERIES 207.

EXTEND $3\frac{1}{2}''$ PEV SUPPLY ABOVE CEILING. PROVIDE SUPPORTS EVERY 4'.

EXTEND $3\frac{1}{2}''$ PEV SUPPLY TO NEW MISTING SYSTEM SOLENOID/MANIFOLD BOX ON TOP OF CASE. SEE ARCHITECTURE PLANS FOR MISTING SYSTEM ISOMETRIC.

EXTEND $2\frac{1}{2}''$ CW SUPPLY CONCEALED IN WALL DOWN TO 4" ABOVE CASE FOR CASE WASH-DOWN. PROVIDE $3\frac{1}{2}''$ FTT BAL VALVE AND DOUBLE CHECK VALVE AT CONNECTION OF EXISTING CW SUPPLY. TERMINATE WITH $3\frac{1}{2}''$ FTT BAL VALVE AND DISCONNECT DISSEMINATE EXACT LOCATION WITH CONSTRUCTION SUPERVISOR. DOUBLE CHECK VALVE ASSEMBLY SHALL BE EQUAL TO A WATTS SERIES 207. ALL PIPING AND ACCESSORIES SHALL BE CONCEALED FROM SALES FLOOR.

INSTALL NEW TWO COMPARTMENT PRODUCE PREP SINK (P=29). EXTEND EXISTING $2\frac{1}{2}''$ CW/HW LINE IN WALL TO NEW PREP SINK. SEE GENERAL NOTE No. 4. REPAIR WALL TO MATCH EXISTING.

EXTEND $2\frac{1}{2}''$ CW SUPPLY TO NEW WALL MOUNTED MAX FRESH. VERIFY LOCATION WITH CONSTRUCTION SUPERVISOR.

RELOCATE 1 COMPARTMENT DELI/BAKERY CHECKED SINK (P=26) AS INDICATED ON SHEETS P1.01 AND P1.03. VERIFY LOCATION WITH OWNERS. EXTEND $2\frac{1}{2}''$ HW/CW IN PART. HEIGHT WALL AND CONNECT. SEE GENERAL NOTE No. 4. REPAIR WALL TO MATCH EXISTING.

EXTEND $1\frac{1}{2}''$ CW SUPPLY TO NEW RACK OVEN.

EXTEND $2\frac{1}{2}''$ CW/HW IN PART. HEIGHT WALL FOR NEW EYE WASH (P=33). MOUNT MIXING VALVE BELOW EYE WASH. EXTEND $2\frac{1}{2}''$ TEMPERED WATER FROM MIXING VALVE TO EYEWASH. VERIFY LOCATION WITH OWNER PRIOR TO CONSTRUCTION. REPAIR WALL TO MATCH EXISTING.

INSTALL NEW EYE WASH (P=33) AS INDICATED. EXTEND $2\frac{1}{2}''$ CW/HW LINES TO MIXING VALVE. MOUNT MIXING VALVE BELOW EYE WASH. EXTEND $2\frac{1}{2}''$ TEMPERED WATER LINE FROM MIXING VALVE TO EYEWASH. VERIFY LOCATION WITH OWNER PRIOR TO CONSTRUCTION. SEE DETAIL 7/P1-01.

RELOCATE EXISTING WATER CLOSET (P=1.1 A-LT.) WITH TRIP LEVER ON OPPOSITE SIDE OF STALL TO MEET ADA REQUIREMENTS. SEE ARCHITECTURAL PLANS FOR DETAIL. RELOCATING EXISTING WATER CLOSET FOR EXACT LOCATION. REPAIR WALL TO MATCH PIPING AS REQUIRED FOR RECONNECTION. REPAIR WALL TO MATCH EXISTING.

RELOCATE EXISTING WATER CLOSET (P=1.1 A-LT.) TO MEET ADA REQUIREMENTS. SEE ARCHITECTURAL PLANS FOR DETAIL. INDICATING DIMENSIONAL INFORMATION FOR EXACT LOCATION. ADJUST EXISTING WATER CLOSET PIPING AS REQUIRED FOR RECONNECTION. REPAIR WALL TO MATCH EXISTING.

RELOCATE EXISTING URINAL (P=2) TO MEET ADA REQUIREMENTS. SEE ARCHITECTURAL PLANS FOR DETAIL. INDICATING DIMENSIONAL INFORMATION FOR EXACT LOCATION. ADJUST EXISTING CW/HW PIPING AS REQUIRED FOR RECONNECTION. REPAIR WALL TO MATCH EXISTING.

RELOCATE EXISTING LAVATORY (P=3A) TO MEET ADA REQUIREMENTS. SEE ARCHITECTURAL PLANS FOR DETAIL. INDICATING DIMENSIONAL INFORMATION FOR EXACT LOCATION. ADJUST EXISTING CW/HW PIPING AS REQUIRED FOR RECONNECTION. REPAIR WALL TO MATCH EXISTING.

RELOCATE EXISTING LAVATORY (P=3) TO MEET ADA REQUIREMENTS. SEE ARCHITECTURAL PLANS FOR DETAIL. INDICATING DIMENSIONAL INFORMATION FOR EXACT LOCATION. ADJUST EXISTING CW/HW PIPING AS REQUIRED FOR RECONNECTION. REPAIR WALL TO MATCH EXISTING.

INSTALL NEW WATER COOLER (P=4) TO MEET ADA REQUIREMENTS. SEE ARCHITECTURAL PLANS FOR DETAIL. INDICATING DIMENSIONAL INFORMATION FOR EXACT LOCATION. EXTEND EXISTING $2\frac{1}{2}''$ CW SUPPLY AS REQUIRED. REPAIR WALL TO MATCH